

Bending formers and back formers

Accessories for REMS Curvo 50, REMS Curvo, REMS Akku-Curvo 22V and REMS Sinus



Bending formers and back formers, 180°, form and pressure resistant, in high-strength, high-slide, glass-fibre reinforced polyamide 90° (Ø 35 R 100, Ø 42 R 140, Ø 50 R 135, Ø 1" R 100, Ø 1½" R 140). Optimum matching of bending former and back former guarantees material-compatible gliding without cracks and creases. Angle scale provided on each bending former and mark on the back former ensure precise bending. Rapid change of bending formers and back formers.

Bending former and back former for pipes Ø mm/inch O.D.	R mm/inch	X mm 90°	X mm 45°	→ REMS Sinus						→ REMS Curvo						→ REMS Akku-Curvo 22V						→ REMS Curvo 50						Art.-No.												
				Cu	Cu-U	St 10312	St 10305-U	St 10305	St 10255	St 50086	V	Cu	Cu 12735	Cu-U	St 10312	St 10305-U	St 10305	St 10255	St 50086	V	Cu	Cu 12735	Cu-U	St 10312	St 10305-U	St 10305	St 10255		St 50086	V	Cu	Cu 12735	Cu-U	St 10312	St 1127	St 10305-U	St 10305	St 10255	St 50086	V
				●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲
10	40/1.57	45	20	●			●			●				●			●			▲				▲												581400				
12	45/1.77	49	22	●		●	●			●			●			●			▲				▲												581410					
14, 10 U, ¼" (DN 6)	50/1.97	53	23	●	●					●			●			●			▲				▲												581420					
15, 12 U	55/2.17	56	25	●		●	●			●			●			●			▲				▲												581430					
16, 12 U	60/2.36	62	28	●	●			●		●			●			●			▲				▲												581440					
17, 15 U	56/2.20	60	27	●						●			●			●			▲				▲												581110					
18, 14 U, 15 U, ⅜" (DN 10)	70/2.76	75	33	●	●	●				●			●			●			▲				▲												581450					
20, 16 U, 18 U	75/2.95	80	36	●	●		●			●			●			●			▲				▲												581080					
21.3, ½" (s = 1.6/2.0/2.6)	103/4.06	110	50																■				■											581480						
22, 18 U, ½" (DN 15)	77/3.03	81	36	●	●					●			●			●			▲				▲												581460					
22, 18 U, ½" (DN 15)	88/3.46	91	41							●			●			●			▲				▲												581470					
24, 22 U	75/2.95	85	38							●			●			●			▲				▲												581130					
25	98/3.86	103	46							●			●			●			▲				▲												581180					
26	98/3.86	108	49							●			●			●			▲				▲												581270					
26.9, ¾" (s = 1.6/2.0/2.6)	102/4.02	108	49							●			●			●			▲				▲												581490					
28 ¹⁾	102 ³⁾ /4.02	108	49							●			●			●			▲				▲												581070					
28, ¾" (DN 20) ²⁾	102/4.02	110	50							●			●			●			▲				▲												581260					
28, ¾" (DN 20) ²⁾	114/4.49	120	54							●			●			●			▲				▲												581310					
30, 28 U	98/4.02	105	47							●			●			●			▲				▲												581150					
32	98/4.02	110	50							●			●			●			▲				▲												581280					
32	114/4.49	121	54							●			●			●			▲				▲												581320					
1" (DN 25)	100/3.94	105	47							●			●			●			▲				▲												581520					
33.7, 1" (s = 1.6/2.0/2.6)	100/3.94	105	47							●			●			●			▲				▲												581520					
35	100/3.94	105	47							●			●			●			▲				▲												581500					
35	140/5.51	150	68							●			●			●			▲				▲												581350					
40	140/5.51	148	67							●			●			●			▲				▲												581330					
42	140/5.51	155	70							●			●			●			▲				▲												581510					
1¼" (DN 32)	140/5.51	150	68							●			●			●			▲				▲												581530					
42.4, 1½" (s = 2.0/2.6)	140/5.51	150	68							●			●			●			▲				▲												581530					
50	135/5.38	143	64							●			●			●			▲				▲												581540					
¾" (9.5 mm)	43/1.69	48	22	●						●			●			●			▲				▲												581200					
½" (12.7 mm)	52/2.05	60	27	●						●			●			●			▲				▲												581210					
⅝" (15.9 mm)	63/2.48	70	32							●			●			●			▲				▲												581220					
¾" (19.1 mm)	75/2.95	82	37	●						●			●			●			▲				▲												581230					
⅞" (22.2 mm)	98/3.36	107	48	●						●			●			●			▲				▲												581240					
1" (25.4 mm)	101/3.98	112	50							●			●			●			▲				▲												581370					
1⅝" (28.6 mm)	102/4.02	110	44							●			●			●			▲				▲												581260					
1⅞" (28.6 mm)	115/4.53	117	53							●			●			●			▲				▲												581380					
1¼" (31.8 mm)	114/4.49	123	55							●			●			●			▲				▲												581320					
1¼" (31.8 mm)	133/5.24	145	65							●			●			●			▲				▲												581390					
1⅜" (34.9 mm)	100/3.94	105	47							●			●			●			▲				▲												581500					
1⅜" (34.9 mm)	140/5.51	150	68							●			●			●			▲				▲												581350					
1⅝" (41.3 mm)	140/5.51	155	70							●			●			●			▲				▲												581510					

R mm Bending radius mm at the neutral axis of the bend (DVGW GW 392)
 X mm Correction dimension for a 90° or 45° bend
 s mm Wall thickness
 1) hard, semi-hard copper pipes, also thin-walled, EN 1057
 2) hard copper pipes EN 1057
 3) According to DVGW work sheet GW 392 for hard and semi-hard copper pipes
 Ø 28 mm minimum bending radius 114 mm necessary. Wall thickness ≥ 0.9 mm.
 ▲ Adaptor block 10-40, support 10-40 (Art.-No. 582120) necessary.
 ■ Adaptor block 35-50, support 35-50 (Art.-No. 582110) necessary.
 Cu: hard, half-hard, soft copper tubes, also thin-wall, EN 1057
 Cu 12735: Copper pipes K65 for refrigeration and air conditioning technology in accordance with EN 12735-1, EN 12449
 St 10312: stainless steel pipes of the press fitting systems EN 10312, series 2, EN 10088, EN 10217-7
 St 1127: stainless steel pipes EN ISO 1127, EN 10217-7
 St 10305-U: coated, soft carbon steel pipes of the press fitting systems EN 10305-3
 St 10305: soft precision steel pipes EN 10305-1, EN 10305-2, EN 10305-3, carbon steel pipes EN 10305-3
 St 10255: Steel pipes (threaded pipes) EN 10255
 St 50086: Electrical installation pipes DIN EN 50086
 U: coated
 V: multi-layer composite tubes of pressfitting systems

